AC6956A Datasheet

Zhuhai Jieli Technology Co.,LTD

Version：1.0

Date：2019.12.25

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Copyright © Zhuhai Jieli Technology Co.,LTD. All rights reserved.

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

AC6956A Features

High performance 32-bit RISC CPU

- RISC 32-bit CPU
- DC-160MHz operation
- Support DSP instructions
- 64Vectored interrupts
- 4 Levels interrupt priority

Flexible I/O

- 15 GPIO pins
- All GPIO pins can be programmable as input or output individually
- All GPIO pins are internal pull-up/pull-down selectable individually
- CMOS/TTL level Schmitt triggered input
- External wake up/interrupt on all GPIOs

Peripheral Feature

- One full speed USB 2.0 OTG controller
- Four multi-function 16-bit timers, support capture and PWM mode
- Three 16-bit PWM generator for motor driving
- One 16-bit active parallel port
- One full-duplex basic UART
- Two full-duplex advanced UART
- Three SPI interface supports host and device mode
- One SD Card Host controller
- One IIC interface supports host and device mode
- One Quadrate decoder
- Watchdog
- 2 Crystal Oscillator
- 16-bit Stereo DAC with headphone amplifier, SNR >= 95dB
- 3 channel ADC , SNR >= 90dB
- 1 channel MIC amplifier
- Three channels analog MUX
- 9 channels 10-bit ADC
- 2 channels 8 levels Low Voltage Detector
- Power-on reset
- Embedded PMU support low power mode

Bluetooth Feature

- CMOS single-chip fully-integrated radio and baseband
- Compliant with Bluetooth V5.1+BR+EDR+BLE specification
- Bluetooth Piconet and Scatternet support
- Meet class2 and class3 transmitting power requirement
- Support GFSK and π/4 DQPSK all paket types

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

- Provides +6dbm transmitting power
- receiver with -90dBm sensitivity
- Support a2dp\avctp\avdtp\avrcp\hfp\spp\smp\att\gap\gatt\rfcomm\sdp\l2cap profile

Power Supply

- VBAT is 2.2V to 5.5V
- VDDIO is 2.2V to 3.6V

Package

- QFN32_4x4

Temperature

- Operating temperature: -20℃ to +70℃
- Storage temperature: -65℃ to +150℃

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1、Pin Definition

1.1 Pin Assignment




Figure 1-1 AC6956A_QFN32_4x4 Package Diagram

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1.2 Pin Description

Table 1-1 AC6956A_QFN32_4x4 Pin Description

PIN NO.	Name	I/O Type	Drive (mA)	Function	Other Function
1	DACVSS	P	/	Ground	
2	NC				
3	VDDIO	P	/	IO Power 3.3v	
4	PB10	I/O	24/8	GPIO	AMUX2R：Analog Channel2 Right; SPI2DOA：SPI2 Data Out(A); ADC9：ADC Input Channel 9; UART2RXC：Uart2 Data In(C); PWMCH3L：Motor PWM Channel3(L)；
	PB9	I/O	24/8	GPIO	AMUX2L：Analog Channel2 Left; SPI2CLKA：SPI2 Clk(A); CAP0：Timer0 Capture; UART2TXC：Uart2 Data Out(C); PWMCH3H：Motor PWM Channel3(H)；
5	PB8	I/O	24/8	GPIO	AMUX1R：Analog Channel1 Right; SPI2_DIA：SPI2 Data In(A); ADC8：ADC Input Channel 8; CLKOUT1：Clk Out1;
6	PB7	I/O	24/8	GPIO	AMUX1L：Analog Channel1 Left;
	PB4	I/O	24/8	GPIO	IIC_SCL_C：IIC SCL(C); ADC7：ADC Input Channel 7; UART0TXB：Uart0 Data Out(B); LVD：Low Voltage Detect Input; PWMCH2H：Motor PWM Channel2 (H)；
7	VSSIO	P	/	Ground	
8	NC				
9	VBAT	P	/	LDO Power	
10	LDO_IN	P	/	Charge Power 5v	
	PB5	I/O	8	GPIO (High Voltage Resistance)	PWM3：Timer3 PWM Output; CAP1：Timer1 Capture; UART0TXC：Uart0 Data Out(C); UART0RXC：Uart0 Data In(C);
11	BT_AVDD	P	/	BT Power 1.3v	

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

12	PB2	I/O	8	GPIO (High Voltage Resistance)	SPI1DIA：SPI1 Data In(A); PWMCH1L：Motor PWM Channel1 (L)；
13	PB3	I/O	24/8	GPIO	PWM2：Timer2 PWM Output; ADC6：ADC Input Channel 6;
14	PB1	I/O	24/8	GPIO (pull up)	Long Press Reset； SPI1DOA：SPI1 Data Out(A); ADC5：ADC Input Channel 5; TMR2：Timer2 Clock Input; UART1RXA：Uart1 Data In(A);
15	PB0	I/O	8	GPIO (High Voltage Resistance)	SPI1CLKA：SPI1 Clock(A); UART1TXA：Uart1 Data Out(A); PWMCH1H：Motor PWM Channel1(H)；
16	BT_RF	/	/		
17	VSSIO	P	/	Ground	
18	BT_OSCI	I	/	OSC In	
19	BT_OSCO	O	/	OSC Out	
20	PC5	I/O	24/8	GPIO	SD1CLKA：SD1 Clock(A); SPI1DOB：SPI1 Data Out(B); UART2RXD：Uart2 Data In(D); IIC_SDA_B：IIC SDA(B); ADC13：ADC Input Channel 13; PWMCH5L：Motor PWM Channel5(L)；
21	PC4	I/O	24/8	GPIO	SD1CMDA：SD1 Command(A); SPI1CLKB：SPI1 Clock(B); UART2TXD：Uart2 Data Out(D); IIC_SCL_B：IIC SCL(B); ADC10：ADC Input Channel 10; PWMCH5H：Motor PWM Channel5(H)；
22	PC3	I/O	24/8	GPIO	SD1DAT0A：SD1 Data0(A); SPI1DIB：SPI1 Data In(B);
23	DVDD	P	/	Core Power	
24	USBDM	I/O	4	USB Negative Data (pull down)	UART1RXD：Uart1 Data In(D); IIC_SDA_A：IIC SDA(A);
25	USBDP	I/O	4	USB Positive Data (pull down)	UART1TXD：Uart1 Data Out(D); IIC_SCL_A：IIC SCL(A); ADC12：ADC Input Channel 12;
26	PC7	I/O	/	GPIO	MIC_BIAS：Microphone Bias Output
27	PC6	I/O	24/8	GPIO	MIC：MIC Input Channel;

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

					ADC11：ADC Input Channel 11;
28	DACR	O	/		DAC Right Channel
29	DACL	O	/		DAC Left Channel
30	VCOMO	/	/		DAC Reference Output
31	DACVDD	P	/		Power supply for audio DAC logic
32	NC				

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2、Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Tamb	Ambient Temperature	-20	+70	°C
Tstg	Storage temperature	-65	+150	°C
VBAT	Supply Voltage	2.2	5.5	V
LDO_IN	Charger Voltage	4.5	5.5	V
$V_{3.3IO}$	3.3V IO Input Voltage	-0.3	VDDIO+0.3	V

2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.2	3.7	5.5	V	
LDO_IN	Charger Voltage	4.5	5.0	5.5	V	
$V_{3.3}$	Voltage output	_	3.3	_	V	VBAT = 5V, 100mA loading
V_{BT_AVDD}	Voltage output		1.3		V	VBAT=5V, 100mA loading
V_{DACVDD}	DAC Voltage	_	2.7	_	V	VBAT = 5V, 10mA loading
$I_{L3.3}$	Loading current	_	_	150	mA	VBAT = 5V

2.3 Battery Charge

Table 2-3

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
LDO_IN	Charge Input Voltage	4.5	5	5.5	V	_
V_{Charge}	Charge Voltage	4.15	4.2	4.25	V	_
I_{Charge}	Charge Current	20		320	mA	Charge current at fast charge mode
I_{Trikl}	Trickle Charge Current	20	45	70	mA	$V_{BAT} < V_{Trikl}$

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.4 IO Input/Output Electrical Logical Characteristics

Table 2-4

IO input characteristics						
Symbol	**Parameter**	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
V_{IL}	Low-Level Input Voltage	-0.3	_	0.3* VDDIO	V	VDDIO = 3.3V
V_{IH}	High-Level Input Voltage	0.7* VDDIO	_	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V_{OL}	Low-Level Output Voltage	_	_	0.33	V	VDDIO = 3.3V
V_{OH}	High-Level Output Voltage	2.7	_	_	V	VDDIO = 3.3V

2.5 Internal Resistor Characteristics

Table 2-5

Port	**General Output**	**High Drive**	**Internal Pull-Up Resistor**	**Internal Pull-Down Resistor**	**Comment**
PB0~PB10 PC6	8mA	24mA	10K	10K	1、PB1 default pull up 2、USBDM & USBDP default pull down 3、internal pull-up/pull-down resistance | accuracy ±20%
PC7			10K	10K	
PB5			10K	10K	
USBDP	4mA	_	1.5K	15K	
USBDM	4mA		180K	15K	

2.6 DAC Characteristics

Table 2-6

Parameter	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
Frequency Response	20	_	20K	Hz	1KHz/0dB 10Kohm loading With A-Weighted Filter
THD+N	_	-75	_	dB	
S/N	_	95	_	dB	
Crosstalk	_	-80	_	dB	
Output Swing		1		Vrms	
Dynamic Range		90		dB	1KHz/-60dB 10Kohm loading With A-Weighted Filter
DAC Output Power	11		_	mW	32ohm loading

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.7 ADC Characteristics

Table 2-7

Parameter	Min	Typ	Max	Unit	Test Conditions
Dynamic Range		80		dB	1KHz/-60dB
S/N	_	90	91	dB	1KHz/-60dB
THD+N	_	-70	_	dB	
Crosstalk	_	-80	_	dB	

2.8 BT Characteristics

2.8.1 Transmitter

Basic Data Rate **Table 2-8**

Parameter		Min	Typ	Max	Unit	Test Conditions
RF Transmit Power			4	6	dBm	25℃, Power Supply VBAT=5V 2441MHz
RF Power Control Range			20		dB	
20dB Bandwidth			950		KHz	
Adjacent Channel Transmit Power	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

Enhanced Data Rate **Table 2-9**

Parameter		Min	Typ	Max	Unit	Test Conditions
Relative Power			-1		dB	25℃, Power Supply VBAT=5V 2441MHz
π/4 DQPSK Modulation Accuracy	DEVM RMS		6		%	
	DEVM 99%		10		%	
	DEVM Peak		15		%	
Adjacent Channel Transmit Power	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.8.2 Receiver

Basic Data Rate **Table 2-10**

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	25℃, Power Supply VBAT=5V 2441MHz
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

Enhanced Data Rate **Table 2-11**


Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	25℃, Power Supply VBAT=5V 2441MHz
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3、 Package Information

3.1 QFN32_4x4



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0	0.02	0.05
b	0.15	0.20	0.25
c	0.18	0.20	0.25
D	3.90	4.00	4.10
D2	2.60	2.65	2.70
e	0.40BSC		
Nd	2.80BSC		
E	3.90	4.00	4.10
E2	2.60	2.65	2.70
Ne	2.80BSC		
K	0.20	–	–
L	0.35	0.40	0.45
L1	0.30	0.35	0.40
L2	0.15	0.20	0.25
h	0.30	0.35	0.40
L/F载体尺寸 (mil)	112*112		

Figure 3-1 AC6956A_QFN32_4x4 Package

ZHUHAI JIELI TECHNOLOGY

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

4、Revision History

Date	Revision	Description
2019.12.25	V1.0	Initial Release

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.