AC6956F Datasheet

Zhuhai Jieli Technology Co.,LTD

Version：1.0

Date：2020.01.15

Copyright © Zhuhai Jieli Technology Co.,LTD. All rights reserved.

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

AC6956F Features

CPU

- 32-bit DSP supports hardware Float Point Unit(FPU)
- Up to 240MHz programmable processor
- 64Vectored interrupts
- 4 Levels interrupt priority

DSP Audio Processing

- SBC, AAC Audio decodes supported for BT audio
- mSBC voice codecs supported for BT phone
- Supports MP2, MP3, WMA, APE, FLAC, AAC, MP4, M4A, WAV, AIF, AIFC audio decoding
- Packet Loss Concealment (PLC) for voice processing
- Acoustic echo cancellation/suppression (AEC,AES)
- Single/Dual MIC Environmental Noise Cancellation (ENC)
- Multi-band DRC limiter
- 30-band EQ configuration for voice Effects

Audio Codec

- Four channels 16-bit DAC, SNR >= 95dB
- Three channels 16-bit ADC , SNR >= 90dB
- Sampling rates of 8KHz/11.025KHz/16KHz/22.05KHz/24KHz/ 32KHz/44.1KHz/48KHz are supported
- One analog MIC amplifier, build-in MIC bias generator
- Supports two PDM digital MIC inputs
- three channels Stereo analog MUX
- Supports cap-less, single-ended, and differential mode at the DAC path
- Supports 16ohm and 32ohm Speaker loading

Bluetooth

- Compliant with Bluetooth V5.1+BR+EDR+BLE specification
- Meet class1 class2 and class3 transmitting power requirement
- Support GFSK and π/4 DQPSK all paket types
- Provides +6dbm transmitting power
- receiver with -90dBm sensitivity
- Fast AGC for enhanced dynamic range
- Supports a2dp\avctp\avdtp\avrcp\hfp\spp\smp\att\gap\gatt\rfcomm\sdp\l2cap profile

Peripherals

- One full speed USB 2.0 OTG controller
- Four multi-function 16-bit timers, support capture and PWM mode
- Three 16-bit PWM generator for motor driving
- Three full-duplex basic UART, UART0 and UART1 supports DMA mode
- Two SPI interface supports host and device mode
- Two SD Card Host controller
- One hardware IIC interface supports host and device mode
- Built-in Cap Sense Key controller
- 9 channels 10-bit ADC for analog sampling
- External wake up/interrupt on all GPIOs

PMU

- Low voltage LDO for internal digital and analog circuit supply
- 1uA current consumption in the soft-off mode
- Built-in LDO for the core, I/O, Bluetooth and flash
- VBAT is 2.2V to 5.5V
- VDDIO is 2.2V to 3.6V
- RTCVDD is 2.2V to 3.6V

Packages

- QFN32(4mm*4mm)

Temperature

- Operating temperature: -20℃ to +70℃

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

- Storage temperature: -65℃ to +150℃

Applications

- Bluetooth Stereo headset
- Bluetooth Mono headset

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1、Pin Definition

1.1 Pin Assignment




Figure 1-1 AC6956F_QFN32_4x4 Package Diagram

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1.2 Pin Description

Table 1-1 AC6956F_QFN32_4x4 Pin Description

PIN NO.	Name	I/O Type	Drive (mA)	Function	Other Function
1	DACRL	O	/		DAC Rear Left Channel
2	DACRR	O	/		DAC RearRight Channel
3	DACFL	O	/		DAC Front Left Channel
4	DACFR	O	/		DAC FrontRight Channel
5	NC				
6	PB11	I/O	/	GPIO	SDPG:SDC Power Gate;
7	PB10	I/O	24/8	GPIO	AMUX2R：Analog Channel2 Right; SD0CMB：SD0 Command(B); SPI2DOA：SPI2 Data Out(A); SD1DAT3B：SD1 Data3(B); ADC9：ADC Input Channel 9; UART2RXC：Uart2 Data In(C); PWMCH3L：Motor PWM Channel3(L)；
8	PB9	I/O	24/8	GPIO	AMUX2L：Analog Channel2 Left; SD0CLKB：SD0 Clock(B); SPI2CLKA：SPI2 Clk(A); SD1DAT2B：SD1 Data2(B); CAP0：Timer0 Capture; UART2TXC：Uart2 Data Out(C); PWMCH3H：Motor PWM Channel3(H)；
9	PB8	I/O	24/8	GPIO	AMUX1R：Analog Channel1 Right; SD0DAT0B：SD0 Data0(B); SPI2_DIA：SPI2 Data In(A); SD1DAT1B：SD1 Data1(B); ADC8：ADC Input Channel 8; CLKOUT1：Clk Out1;
10	LDO_IN	P	/	Charge Power 5v	
	PB5	I/O	/	GPIO (High Voltage Resistance)	PWM3：Timer3 PWM Output; CAP1：Timer1 Capture; UART0TXC：Uart0 Data Out(C); UART0RXC：Uart0 Data In(C);
11	VBAT	P	/	LDO Power	
12	BT_AVDD	P	/	BT Power 1.3v	

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

13	PB3	I/O	24/8	GPIO	PWM2：Timer2 PWM Output; ADC6：ADC Input Channel 6;
14	PB1	I/O	24/8	GPIO (pull up)	Long Press Reset； SPI1DOA：SPI1 Data Out(A); ADC5：ADC Input Channel 5; TMR2：Timer2 Clock Input; UART1RXA：Uart1 Data In(A);
15	PB0	I/O	8	GPIO (High Voltage Resistance)	SPI1CLKA：SPI1 Clock(A); UART1TXA：Uart1 Data Out(A); PWMCH1H：Motor PWM Channel1(H)；
16	BT_RF	/	/		
17	BT_OSCI	I	/	OSC In	
18	BT_OSCO	O	/	OSC Out	
19	PC5	I/O	24/8	GPIO	SD1CLKA：SD1 Clock(A); SPI1DOB：SPI1 Data Out(B); UART2RXD：Uart2 Data In(D); IIC_SDA_B：IIC SDA(B); ADC13：ADC Input Channel 13; PWMCH5L：Motor PWM Channel5(L)；
20	PC4	I/O	24/8	GPIO	SD1CMDA：SD1 Command(A); SPI1CLKB：SPI1 Clock(B); UART2TXD：Uart2 Data Out(D); IIC_SCL_B：IIC SCL(B); ADC10：ADC Input Channel 10; PWMCH5H：Motor PWM Channel5(H)；
21	PC3	I/O	24/8	GPIO	SD1DAT0A：SD1 Data0(A); SPI1DIB：SPI1 Data In(B);
22	USBDM	I/O	4	USB Negative Data (pull down)	UART1RXD：Uart1 Data In(D); IIC_SDA_A：IIC SDA(A);
23	USBDP	I/O	4	USB Positive Data (pull down)	UART1TXD：Uart1 Data Out(D); IIC_SCL_A：IIC SCL(A); ADC12：ADC Input Channel 12;
24	PA10	I/O	24/8	GPIO	SD0CLKA：SD0 Clock(A); ADC3：ADC Input Channel 3; Touch9：Touch Input Channel 9; UART2RXB：Uart2 Data In(B); PWMCH4L：Motor PWM Channel4(L)；
25	PA9	I/O	24/8	GPIO	SD0CMA：SD0 Command(A); Touch8：Touch Input Channel 8;

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

					UART2TXB：Uart2 Data Out(B); PWMCH4H：Motor PWM Channel4(H)；
26	PA1	I/O	24/8	GPIO	AMUX0R：Analog Channel0 Right; Touch1：Touch Input Channel 1; ADC0：ADC Input Channel 0; UART1RXC：Uart1 Data In(C); PWMCH0L：Motor PWM Channel0(L)；
27	PA0	I/O	24/8	GPIO	AMUX0L：Analog Channel0 Left; Touch0：Touch Input Channel 0; CLKOUT0： UART1TXC：Uart1 Data Out(C); PWMCH0H：Motor PWM Channel0(H)；
28	PC7	I/O	/	GPIO	MIC_BIAS：Microphone Bias Output
29	PC6	I/O	24/8	GPIO	MIC：MIC Input Channel; ADC11：ADC Input Channel 11;
30	VDDIO	P	/	IO Power 3.3v	
31	DACVSS	P	/		DAC Ground
32	VCOM	P	/		DAC Reference

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2、Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Tamb	Ambient Temperature	-20	+70	°C
Tstg	Storage temperature	-65	+150	°C
VBAT	Supply Voltage	2.2	5.5	V
LDO_IN	Charger Voltage	4.5	5.5	V
$V_{3.3IO}$	3.3V IO Input Voltage	-0.3	VDDIO+0.3	V

2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.2	3.7	5.5	V	
LDO_IN	Charger Voltage	4.5	5.0	5.5	V	
$V_{3.3}$	Voltage output	_	3.3	_	V	VBAT = 5V, 100mA loading
V_{BT_AVDD}	Voltage output		1.3		V	VBAT=5V, 100mA loading
$I_{L3.3}$	Loading current	_	_	150	mA	VBAT = 5V

2.3 Battery Charge

Table 2-3

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
LDO_IN	Charge Input Voltage	4.5	5	5.5	V	_
V_{Charge}	Charge Voltage	4.15	4.2	4.25	V	_
I_{Charge}	Charge Current	20		320	mA	Charge current at fast charge mode
I_{Trikl}	Trickle Charge Current	20	45	70	mA	$V_{BAT}<V_{Trikl}$

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.4 IO Input/Output Electrical Logical Characteristics

Table 2-4

IO input characteristics						
Symbol	**Parameter**	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
V_{IL}	Low-Level Input Voltage	-0.3	_	0.3* VDDIO	V	VDDIO = 3.3V
V_{IH}	High-Level Input Voltage	0.7* VDDIO	_	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V_{OL}	Low-Level Output Voltage	_	_	0.33	V	VDDIO = 3.3V
V_{OH}	High-Level Output Voltage	2.7	_	_	V	VDDIO = 3.3V

2.5 Internal Resistor Characteristics

Table 2-5

Port	**General Output**	**High Drive**	**Internal Pull-Up Resistor**	**Internal Pull-Down Resistor**	**Comment**
PB0~PB10 PC6	8mA	24mA	10K	10K	1、PB1 default pull up 2、USBDM & USBDP default pull down 3、internal pull-up/pull-down resistance | accuracy ±20%
PA0~PA10			10K	10K	
PB5 PC7			10K	10K	
USBDP	4mA	_	1.5K	15K	
USBDM	4mA		180K	15K	

2.6 DAC Characteristics

Table 2-6

Parameter	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
Frequency Response	20	_	20K	Hz	1KHz/0dB 10Kohm loading With A-Weighted Filter
THD+N	_	-75	_	dB	
S/N	_	95	_	dB	
Crosstalk	_	-80	_	dB	
Output Swing		1		Vrms	
Dynamic Range		90		dB	1KHz/-60dB 10Kohm loading With A-Weighted Filter
DAC Output Power	11		_	mW	32ohm loading

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.7 ADC Characteristics

Table 2-7

Parameter	Min	Typ	Max	Unit	Test Conditions
Dynamic Range		80		dB	1KHz/-60dB
S/N	_	90	91	dB	1KHz/-60dB
THD+N	_	-70	_	dB	
Crosstalk	_	-80	_	dB	

2.8 BT Characteristics

2.8.1 Transmitter

Basic Data Rate **Table 2-8**

Parameter		Min	Typ	Max	Unit	Test Conditions
RF Transmit Power			4	6	dBm	25℃, Power Supply VBAT=5V 2441MHz
RF Power Control Range			20		dB	
20dB Bandwidth			950		KHz	
Adjacent Channel Transmit Power	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

Enhanced Data Rate **Table 2-9**

Parameter		Min	Typ	Max	Unit	Test Conditions
Relative Power			-1		dB	25℃, Power Supply VBAT=5V 2441MHz
π/4 DQPSK Modulation Accuracy	DEVM RMS		6		%	
	DEVM 99%		10		%	
	DEVM Peak		15		%	
Adjacent Channel Transmit Power	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.8.2 Receiver

Basic Data Rate **Table 2-10**

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	25℃, Power Supply VBAT=5V 2441MHz
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

Enhanced Data Rate **Table 2-11**


Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	25℃, Power Supply VBAT=5V 2441MHz
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3、 Package Information

3.1 QFN32_4x4



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0	0.02	0.05
b	0.15	0.20	0.25
c	0.18	0.20	0.25
D	3.90	4.00	4.10
D2	2.60	2.65	2.70
e	0.40BSC		
Nd	2.80BSC		
E	3.90	4.00	4.10
E2	2.60	2.65	2.70
Ne	2.80BSC		
K	0.20	–	–
L	0.35	0.40	0.45
L1	0.30	0.35	0.40
L2	0.15	0.20	0.25
h	0.30	0.35	0.40
L/F载体尺寸 (MIL)	112*112		

Figure 3-1 AC6956F_QFN32_4x4 Package

ZHUHAI JIELI TECHNOLOGY

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

4、Revision History

Date	Revision	Description
2020.01.16	V1.0	Initial Release

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.