AC6956M Datasheet

Zhuhai Jieli Technology Co.,LTD

Version：V1.1

Date：2023.11.28

Copyright © Zhuhai Jieli Technology Co.,LTD. All rights reserved.

AC6956M Features

CPU

- 32-bit DSP supports hardware Float Point Unit(FPU)
- Up to 240MHz programmable processor
- 64Vectored interrupts
- 4 Levels interrupt priority

DSP Audio Processing

- SBC, AAC Audio decodes supported for BT audio
- mSBC voice codecs supported for BT phone
- Supports MP2, MP3, WMA, APE, FLAC, AAC, MP4, M4A, WAV, AIF, AIFC audio decoding
- Packet Loss Concealment (PLC) for voice processing
- Acoustic echo cancellation/suppression (AEC,AES)
- Single/Dual MIC Environmental Noise Cancellation (ENC)
- Multi-band DRC limiter
- 30-band EQ configuration for voice Effects

Audio Codec

- Four channels 16-bit DAC, SNR >= 95dB
- Three channels 16-bit ADC , SNR >= 90dB
- Sampling rates of 8KHz/11.025KHz/16KHz/22.05KHz/24KHz/ 32KHz/44.1KHz/48KHz are supported
- One analog MIC amplifier, build-in MIC bias generator
- Supports two PDM digital MIC inputs
- three channels Stereo analog MUX
- Supports cap-less, single-ended, and differential mode at the DAC path
- Supports 16ohm and 32ohm Speaker loading

Bluetooth

- Compliant with Bluetooth V5.4+BR+EDR+BLE specification （QDID：223418）
- Meet class2 and class3 transmitting power requirement
- Support GFSK and π/4 DQPSK all packet types
- Provides maximum +6dBm transmitting power
- receiver with minimum -90dBm sensitivity
- Fast AGC for enhanced dynamic range
- Supports a2dp\avctp\avdtp\avrcp\hfp\spp\smp\att\gap\ gatt\rfcomm\sdp\l2cap profile
- a2dp 1.4\avctp 1.4\avdtp 1.3\ avrcp 1.6.2\ hfp 1.8 \spp 1.2\rfcomm 1.2\pnp 1.3\ hid 1.1.1\sdp core5.4\l2cap core 5.4

Peripherals

- One full speed USB 2.0 OTG controller
- Four multi-function 16-bit timers, support capture and PWM mode
- Three 16-bit PWM generator for motor driving
- Three full-duplex basic UART, UART0 and UART1 supports DMA mode
- Two SPI interface supports host and device mode
- SD Card Host controller
- One hardware IIC interface supports host and device mode
- Built-in Cap Sense Key controller
- 10-bit ADC for analog sampling
- External wake up/interrupt on all GPIOs

PMU

- Low voltage LDO for internal digital and analog circuit supply
- Built-in Li-Ion battery charger with up to 200mA charger current capability
- 3uA current consumption in the soft-off mode
- Built-in LDO for the core, I/O, Bluetooth and flash

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

- VBAT is 2.2V to 4.5V
- VDDIO is 2.2V to 3.6V

Packages

- QFN32(4mm*4mm)

Temperature

- Operating temperature: -40℃ to +85℃
- Storage temperature: -65℃ to +150℃

Applications

- Bluetooth Dongle

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1、Pin Definition

1.1 Pin Assignment




Figure 1-1 AC6956M Package Diagram

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1.2 Pin Description

Table 1-1 AC6956M Pin Description

PIN NO.	Name	I/O Type	Drive (mA)	Function	Other Function
1	VCOM	P	/		DAC Reference
2	DACL	O	/		DAC Left Channel
3	DACR	O	/		DAC Right Channel
4	PB11	I/O	/	GPIO	SDPG:SDC Power Gate; SPDIF_OUT：Sony/Philips Digital Interface Out
5	PB10	I/O	8/24	GPIO	AMUX2R：Analog Channel2 Right; SD0CMB：SD0 Command(B); SPI2DOA：SPI2 Data Out(A); ADC9：ADC Input Channel 9; UART2RXC：Uart2 Data In(C); PWMCH3L：Motor PWM Channel3(L)；
6	PB9	I/O	8/24	GPIO	AMUX2L：Analog Channel2 Left; SD0CLKB：SD0 Clock(B); SPI2CLKA：SPI2 Clk(A); CAP0：Timer0 Capture; UART2TXC：Uart2 Data Out(C); PWMCH3H：Motor PWM Channel3(H)；
7	PB8	I/O	8/24	GPIO	AMUX1R：Analog Channel1 Right; SD0DAT0B：SD0 Data0(B); SPI2_DIA：SPI2 Data In(A); ADC8：ADC Input Channel 8; CLKOUT1：Clk Out1;
8	LDO_IN	P	/		Battery Charge Input
	PB5	I/O	8	GPIO (High Voltage Resistance)	PWM3：Timer3 PWM Output; CAP1：Timer1 Capture; UART0TXC：Uart0 Data Out(C); UART0RXC：Uart0 Data In(C);
9	VBAT	P	/		Power Supply
10	VDDIO	P	/		IO Power 3.3v
11	BT_AVDD	P	/		BT Power
12	PB3	I/O	8/24	GPIO	PWM2：Timer2 PWM Output; ADC6：ADC Input Channel 6;
13	PB2	I/O	8	GPIO (High Voltage	SPI1DIA：SPI1 Data In(A); PWMCH1L：Motor PWM Channel1 (L)；

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

				Resistance)	
14	PB1	I/O	8/24	GPIO (pull up)	Long Press Reset； SPI1DOA：SPI1 Data Out(A); ADC5：ADC Input Channel 5; TMR2：Timer2 Clock Input; UART1RXA：Uart1 Data In(A);
15	PB0	I/O	8	GPIO (High Voltage Resistance)	SPI1CLKA：SPI1 Clock(A); UART1TXA：Uart1 Data Out(A); PWMCH1H：Motor PWM Channel1(H)；
16	BT_RF	/	/		BT Antenna
17	BT_OSCI	I	/	OSC In	
18	BT_OSCO	O	/	OSC Out	
19	PC3	I/O	8/24	GPIO	SPI1DIB：SPI1 Data In(B); Touch13：Touch Input Channel 13;
20	PC2	I/O	8/24	GPIO	Touch12：Touch Input Channel 12; FPIN5：Motor Auto-Stop Protective Pin5；
21	PC1	I/O	8/24	GPIO	Touch11：Touch Input Channel 11; UART1RXB：Uart1 Data In(B); FPIN4：Motor Auto-Stop Protective Pin4；
22	PC0	I/O	8/24	GPIO	Touch10：Touch Input Channel 10; UART1TXB：Uart1 Data Out(B); FPIN3：Motor Auto-Stop Protective Pin3；
23	USBDM	I/O	4	USB Negative Data (pull down)	UART1RXD：Uart1 Data In(D); IIC_SDA_A：IIC SDA(A);
24	USBDP	I/O	4	USB Positive Data (pull down)	UART1TXD：Uart1 Data Out(D); IIC_SCL_A：IIC SCL(A); ADC12：ADC Input Channel 12;
25	PA10	I/O	8/24	GPIO	ALNK0_LRCKB：Audio Link Word Select(B); ADC3：ADC Input Channel 3; SPDIF_IN_B：Sony/Philips Digital Interface Input(B); LNA_EN; TMR1：Timer1 Clock Input; Touch9：Touch Input Channel 9; UART2RXB：Uart2 Data In(B); PWMCH4L：Motor PWM Channel4(L)；
26	PA9	I/O	8/24	GPIO	SPDIF_IN_A：Sony/Philips Digital Interface Input(A); PA_EN Touch8：Touch Input Channel 8; UART2TXB：Uart2 Data Out(B);

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

					PWMCH4H：Motor PWM Channel4(H)；
27	DVDD	P	/		Core Power
28	PA1	I/O	8/24	GPIO	AMUX0R：Analog Channel0 Right; Touch1：Touch Input Channel 1; ADC0：ADC Input Channel 0; UART1RXC：Uart1 Data In(C); PWMCH0L：Motor PWM Channel0(L)；
29	PA0	I/O	8/24	GPIO	AMUX0L：Analog Channel0 Left; Touch0：Touch Input Channel 0; CLKOUT0： UART1TXC：Uart1 Data Out(C); PWMCH0H：Motor PWM Channel0(H)；
30	PC7	I/O	/	GPIO	MIC_BIAS：Microphone Bias Output
31	MIC	I	/		MIC：MIC Input Channel;
32	DACVSS	P	/		DAC Ground
BOM	GND	P	/		Ground

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2、Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Topt	Operating temperature	-40	+85	℃
Tstg	Storage temperature	-65	+150	℃
VBAT	Supply Voltage	-0.3	4.5	V
LDO5v	Charger Voltage	-0.3	6.5	V
$V_{3.3IO}$	3.3V IO Input Voltage	-0.3	VDDIO+0.3	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below

2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.2	3.7	4.5	V	
LDO_IN	Charger Voltage	4.5	5.0	5.5	V	
$V_{3.3}$	Voltage output	_	3.3	_	V	VBAT = 4.2V, 100mA loading
V_{BT_AVDD}	Voltage output	_	1.3	_	V	VBAT=4.2V, 100mA loading
$I_{L3.3}$	Loading current	_	_	150	mA	VBAT = 4.2V

2.3 Battery Charge

Table 2-3

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
LDO_IN	Charge Input Voltage	4.5	5	5.5	V	_
V_{Charge}	Charge Voltage	4.15	4.2	4.25	V	LDO_IN＞4.5V
I_{Charge}	Charge Current	20		320	mA	Charge current at fast charge mode
I_{Trikl}	Trickle Charge Current	20	45	70	mA	V_{BAT}<V_{Trikl}

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.4 IO Input/Output Electrical Logical Characteristics

Table 2-4

IO input characteristics						
Symbol	**Parameter**	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
V_{IL}	Low-Level Input Voltage	-0.3	_	0.3* VDDIO	V	VDDIO = 3.3V
V_{IH}	High-Level Input Voltage	0.7* VDDIO	_	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V_{OL}	Low-Level Output Voltage	_	_	0.33	V	VDDIO = 3.3V
V_{OH}	High-Level Output Voltage	2.7	_	_	V	VDDIO = 3.3V

2.5 Internal Resistor Characteristics

Table 2-5

Port		**General Output**	**High Drive**	**Internal Pull-Up Resistor**	**Internal Pull-Down Resistor**	**Comment**
PA0、PA1 PA9、PA10 PB1、PB3 PB8~PB10 PC0~PC3		8mA	24mA	10K	10K	1、PB1 default pull up 2、USBDM & USBDP default pull down 3、PB0, PB2, PB5 can pull-up resistance to 5V 4、internal pull-up/pull-down resistance | accuracy ±20% 5、PRx supply by RTCVDD
PB11 PC7	Output 0	8mA	24mA	10K	10K	
	Output 1	8mA	64mA			
PB0、PB2、PB5		8mA	_	10K	10K	
USBDP		4mA	_	1.5K	15K	
USBDM		4mA	_	180K	15K	

2.6 DAC Characteristics

Table 2-6

Parameter	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
Frequency Response	20	_	20K	Hz	1KHz/0dB 10Kohm loading With A-Weighted Filter
THD+N	_	-75	_	dB	
S/N	_	95	_	dB	
Crosstalk	_	-90	_	dB	
Output Swing		1		Vrms	
Dynamic Range		95		dB	1KHz/-60dB 10Kohm loading

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

					With A-Weighted Filter
DAC Output Power		20	_	mW	16ohm loading

2.7 ADC Characteristics

Table 2-7

Parameter	Min	Typ	Max	Unit	Test Conditions
Dynamic Range		80		dB	Fsample=44.1kHz Fin=1KHz 2mVpp Input
S/N	_	90	91	dB	Fsample=44.1kHz Fin=1KHz 1.2Vpp Input
THD+N	_	-70	_	dB	
Crosstalk	_	-90	_	dB	

2.8 BT Characteristics

2.8.1 Transmitter

Basic Data Rate **Table 2-8**

Parameter		Min	Typ	Max	Unit	Test Conditions
RF Transmit Power			4	6	dBm	25℃, Power Supply VBAT=3.7V 2441MHz
RF Power Control Range			20		dB	
20dB Bandwidth			950		KHz	
Adjacent Channel Transmit Power	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

Enhanced Data Rate **Table 2-9**

Parameter		Min	Typ	Max	Unit	Test Conditions
Relative Power			-1		dB	25℃, Power Supply VBAT=3.7V 2441MHz
π/4 DQPSK Modulation Accuracy	DEVM RMS		6		%	
	DEVM 99%		10		%	
	DEVM Peak		15		%	
Adjacent Channel Transmit Power	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.8.2 Receiver

Basic Data Rate **Table 2-10**

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	25℃, Power Supply VBAT=3.7V 2441MHz
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

Enhanced Data Rate **Table 2-11**


Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	25℃, Power Supply VBAT=3.7V 2441MHz
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3、 Package Information

3.1 QFN32_4x4



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0	0.02	0.05
b	0.15	0.20	0.25
c	0.18	0.20	0.25
D	3.90	4.00	4.10
D2	2.60	2.65	2.70
e	0.40BSC		
Nd	2.80BSC		
E	3.90	4.00	4.10
E2	2.60	2.65	2.70
Ne	2.80BSC		
K	0.20	–	–
L	0.35	0.40	0.45
L1	0.30	0.35	0.40
L2	0.15	0.20	0.25
h	0.30	0.35	0.40
L/F载体尺寸 (mil)	112*112		

Figure 3-1 AC6956M Package

ZHUHAI JIELI TECHNOLOGY

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

4、Revision History

Date	Revision	Description
2023.09.11	V1.0	Initial Release
2023.11.28	V1.1	Update Bluetooth Vision and profile

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.